



US 20040075381A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0075381 A1**
(43) **Pub. Date: Apr. 22, 2004**
Burroughes et al.(54) **ELECTROLUMINESCENT DEVICES**(75) **Inventors:** **Jeremy Henley Burroughes**,
Cambridge (GB); **Richard Henry**
Friend, Cambridge (GB); **Christopher**
John Bright, Huntingdon
Cambridgeshire (GB); **David John**
Lacey, Hertfordshire (GB); **Peter**
Devine, Cambridge (GB)

Correspondence Address:
FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER
LLP
1300 I STREET, NW
WASHINGTON, DC 20005 (US)

(73) **Assignee:** **Cambridge Display Technology Lim-**
ited(21) **Appl. No.:** **10/682,204**(22) **Filed:** **Oct. 10, 2003****Related U.S. Application Data**(63) Continuation of application No. 09/508,367, filed on
Jan. 3, 2002, filed as 371 of international application
No. PCT/GB99/00741, filed on Mar. 12, 1999.(30) **Foreign Application Priority Data**

Mar. 18, 1998 (GB) 9805476.0

Publication Classification(51) **Int. Cl.⁷** **H01J 1/62**; H01J 63/04;
H01L 21/00
(52) **U.S. Cl.** **313/504**; 313/483; 438/99;
438/22(57) **ABSTRACT**

An electroluminescent device comprising: a first charge carrier injecting layer for injecting positive charge carriers; a second charge carrier injecting layer for injecting negative charge carriers; and a light-emissive layer located between the charge carrier injecting layers and comprising a mixture of: a first component for accepting positive charge carriers from the first charge carrier injecting layer; a second component for accepting negative charge carriers from the second charge carrier injecting layer; and a third, organic light-emissive component for generating light as a result of combination of charge carriers from the first and second components; at least one of the first, second and third components forming a type II semiconductor interface with another of the first, second and third components.

